



Superior picture quality, superb colour performance

The all-in-one display employs flip-chip COB technology, saving energy while being gentle on the eyes. With DCI-P3 wide colour gamut and 1000000: 1 contrast ratio, it delivers seamless colour transitions and reproduces every detail.

DCI-P3 Colour Gamut 0 10000

1000000: **1** Contrast Ratio







High-precision touch control, inspiration at your fingertips

Supports touch control (compatible with dual systems) using highly precise infrared touch technology. Touch accuracy of ±2mm ensures flexible and accurate interactive operations, enabling natural and smooth writing for more convenient and efficient meetings.

Versatile screen mirroring.

Built-in professional meeting software.

- ➤ Supports wireless screen mirroring for multiple platforms such as Windows, Mac OS, iOS, and Android, displaying up to four screens simultaneously.
- Comes with a meeting whiteboard, video conference and other software, and users can install additional apps as needed.



Multiple display modes, adaptive for all scenarios

Tailored for different meeting environments, offering Standard, Soft, Cinema, and Video modes for optimal display in any setting.



15%

Flexible installation,

easy maintenance

- > Support wall mounting and mobile stand-mounting.
- > Full front maintenance design allows for convenient installation and service.

SPECIFICATIONS

Model	ITV10808COB-V	ITV10808TCH-V	ITV13515COB-V	ITV13515TCH-V	ITV16318COB-V	ITV16318TCH-V	ITV21608COB-V
Display Size	108"	108"	135"	135"	163"	163"	216"
Resolution	1920*1080	1920*1080	1920*1080	1920*1080	1920*1080	1920*1080	3840*2160
Aspect Ratio	16:9	16:9	16:9	16:9	16:9	16:9	16:9
Touch control	No	Infrared touch	No	Infrared touch	No	Infrared touch	No
Overal Dimensions (W x H x D mm)	2410 x 1480 x 31 Bottom Thickness 47mm	2423 x 1487 x 45 Bottom Thickness 47mm	3010 x 1817.5 x 31 Bottom Thickness 47mm	3023 x 1824 x 45 Bottom Thickness 47mm	3610 x 2155 x 31 Bottom Thickness 47mm	3623 x 2161 x 45 Bottom Thickness 47mm	4810 x 2830 x 31 Bottom Thickness 47mm
Actual Screen Dimensions (W x H mm)	2400 x 1350mm	2400 x 1350mm	3000 x 1687.5mm	3000 x 1687.5mm	3600 x 2025mm	3600 x 2025mm	4800 x 2700mm
Installation Method	Mobile Stand/Wall Mounting						Wall Mounting
Refresh Rate(Hz)	3840						
Brightness(nits)	600						
Gray Scale(Bit)	22						
Contrast Ratio	1000000:1						
Viewing Angle(H./V.)	160°/160°						
Maintenance Method	Front						
Operating System	Android 11.0,4+32G						
Working Voltage	AC:100V~240V, 50/60Hz						
Power Consumption Max(W)	1200	1200	1850	1850	2450	2450	4600
Power Consumption AVG(W)	400	400	620	620	820	820	1550
Storage Temp(°C)	-20 ~ 60						
Operating Temp(°C)	-10 ~ 50						
Storage Humidity (%RH)	10 ~ 90						
Operating humidity (%RH)				10 ~ 80			

